

Productname :	DIESEL CLEAN PLUS TRUCK	Creationdate :	31.10.07
Ref.Nr.:	BB17640-3-311007	Replaces:	10.01.07

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : DIESEL CLEAN PLUS TRUCK
Bulk

Application : Additives

Company : CRC Industries Europe bvba
Touwslagerstraat 1
9240 ZELE
Belgium
Tel.: (+32)(0)52/456011
Fax: (+32)(0)52/450034
E-mail : hse@crcind.com

In case of emergency : (+32) (0)52/45 60 11

Subsidiaries		Tel	Fax
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptogatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

2. HAZARD IDENTIFICATION

Health and Safety : Repeated exposure may cause skin dryness or cracking.
The classification for aspiration hazards (R65) does not apply if the liquid preparation has a kinematic viscosity greater or equal to 7 mm²/s at 40°C. (3.2.3. of Annex VI of EU-Directive 67/548)

Environment : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
Distillates (petroleum), hydrotreated light; Kerosine - unspecified	64742-47-8	265-149-8	30-60	Xn	65-66	B
Solvent naphtha (petroleum), light	64742-95-6	265-199-0	10-30	Xn	65	B,P



Productname : DIESEL CLEAN PLUS TRUCK
Ref.Nr.: BB17640-3-311007
Creationdate : 31.10.07
Replaces: 10.01.07

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
arom. (benzene<0.1%)						
branched chain alkaryl hydrocarbon	68784-56-5	272-258-4	5-10	Xn,N	51/53-65-66-67	
polyolefine amide alkyleneamine	(polymer)	-	10-30	-	53	
Explanation notes						
B : substance with national established workplace exposure limit						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

(* Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice : If any symptoms should occur, seek medical advice.

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water

Contact with skin : Wash with water and soap.
Seek medical attention if irritation persists

Inhalation : Fresh air, keep warm and at rest.

Ingestion : If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): 62 °C (Closed Cup)

Explosion limits : upper limit : not available

lower limit : not available

Extinguishing media : water, foam, carbon dioxide or dry agent

Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Ensure adequate ventilation
Shut off all ignition sources

Environmental precautions : Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

Cleaning methods : Absorb spillage in suitable inert material



Productname :	DIESEL CLEAN PLUS TRUCK	Creationdate :	31.10.07
Ref.Nr.:	BB17640-3-311007	Replaces:	10.01.07

7. HANDLING AND STORAGE

Handling procedures : The usual precautions for handling chemicals should be observed
Use only in well ventilated areas
It is advisable to take precautions to avoid contact with skin and eyes when handling the product.
Do not breathe aerosols or vapours.

Storage procedures : Keep in a cool, dry, well ventilated place
Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation

Personal protection :

inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.
(Filter type A)

hands and skin : Wear suitable protective gloves
(nitrile)

eyes : Wear safety goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state : Liquid

colour : colourless

odour : Aromatic

Boiling point/range : not available

Relative density : 0.895 g/cm³ (@ 20°C)

pH : not applicable

Vapour pressure : not available

Relative vapour density : not available

Solubility in water : Insoluble in water

Partition coefficient n-octanol/water: not available

Flash point : 62 °C (Closed Cup)

Auto-ignition : > 200 °C

Viscosity : 20 mPas (@ 40°C)

Evaporation rate : not available

Productname :	DIESEL CLEAN PLUS TRUCK	Creationdate :	31.10.07
Ref.Nr.:	BB17640-3-311007	Replaces:	10.01.07

10. STABILITY AND REACTIVITY

Conditions to be avoided :	Avoid overheating
Materials to be avoided :	Strong oxidising agent
Hazardous decomposition compounds :	CO,CO2

11. TOXICOLOGICAL INFORMATION

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Skin contact :	Prolonged skin contact will result in defatting of the skin

12. ECOLOGICAL INFORMATION

Other adverse effects :	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses
--------------------------------	---

13. WASTE DISPOSAL

Product :	Do not empty into drains. This material and its container must be disposed of in a safe way. Disposal should be in accordance with local, state or national legislation
------------------	---

14. TRANSPORT

Road/Rail - ADR/RID :	---- Not classified
Sea - IMDG :	---- Not classified
Air - IATA/ICAO :	---- Not classified

15. REGULATORY INFORMATION

Risk-phrases(s) :	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or cracking.
Safety-phrases(s) :	S2: Keep out of the reach of children. S23: Do not breathe vapour. S24/25: Avoid contact with skin and eyes. S35: This material and its container must be disposed of in a safe way.

Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons > 30 %



Productname :	DIESEL CLEAN PLUS TRUCK	Creationdate :	31.10.07
Ref.Nr.:	BB17640-3-311007	Replaces:	10.01.07

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

***Explanation risk-phrases:**

R36: Irritating to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website : www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

