Productname :
 ZINC
 Creationdate :
 31.10.07

 Ref.Nr.:
 AB13900-3-311007
 Replaces:
 28.10.05

# 1. IDENTIFICATION OF PRODUCT AND COMPANY

**Productname:** ZINC

Aerosol

**Application:** Anti Corrosion Products

CRC Industries Europe byba

Touwslagerstraat 1

9240 ZELE Belgium

Tel.: (+32)(0)52/456011 Fax: (+32)(0)52/450034 E-mail: <u>hse@crcind.com</u>

In case of emergency: (+32) (0)52/45 60 11

Subsidiaries		Tel	Fax
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptongatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

#### 2. HAZARD IDENTIFICATION

**Health and Safety**: Extremely Flammable

(DME propellant)

Repeated exposure may cause skin dryness or

cracking.

Vapours may cause drowsiness and dizziness.

**Environment**: Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Other hazards: Pressurized container: protect from sunlight and do

not expose to temperatures exceeding 50°C.

## 3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	< 0.1	Xi	10-36	A
dimethyl ether	115-10-6	204-065-8	30-60	F+	12	A
Naphtha (petroleum), hydrotreated	64742-49-0	265-151-9	1-5	Xn	10-65-66-67	B,P



**Productname:** ZINC **Creationdate:** 31.10.07 **Ref.Nr.:** AB13900-3-311007 **Replaces:** 28.10.05

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
light (benzene<0.1%)						
Naphtha (petroleum),						
hydrodesulfurized heavy	64742-82-1	265-185-4	1-5	Xn,N	10-51/53-65-66-67	B,P
(benzene<0.1%)						
zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3	10-30	N	50/53	
butanone; ethyl methyl ketone	78-93-3	201-159-0	<20	F,Xi	11-36-66-67	A
Explanation notes						
A : substance with Community						
workplace exposure limit						
B : substance with national						
established workplace exposure limit						
P: not classified as carcinogen, less						
than 0.1% w/w benzene (Einecs-nr.						
200-753-7)						

Note H and P of Annex I (67/548/EEC) apply for the naphtha's in this product.

Remark: for substances with workplace exposure limits see point 8.

(\* Explanation risk-phrases : see chapter 16)

#### 4. FIRST AID MEASURES

**General Advice**: If symptoms persist always call a doctor

**Contact with eyes:** If substance has got into eyes, immediately wash out

with plenty of water for several minutes

Seek medical advice

**Contact with skin**: Wash with water and soap.

**Inhalation**: Fresh air, keep warm and at rest.

Seek medical attention if ill effects occur

**Ingestion**: Ingestion is unlikely to occur

If swallowed accidentally, do not induce vomiting and

seek medical advice.

## 5. FIRE-FIGHTING MEASURES

Flash point (without propellant): < 0 °C

**Explosion limits : upper limit :** not available **lower limit :** not available

**Extinguishing media:** foam, carbon dioxide or dry agent

**Fire-fighting procedures**: Keep container(s) exposed to fire cool, by spraying

with water

**Unusual exposure hazard :** Aerosols may explode if heated above 50°C

In case of fire, do not breathe fumes



 Productname :
 ZINC
 Creationdate :
 31.10.07

 Ref.Nr.:
 AB13900-3-311007
 Replaces:
 28.10.05

6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Shut off all ignition sources

Ensure adequate ventilation

**Environmental precautions:** Do not allow to enter public sewers and watercourses

If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

**Cleaning methods:** Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

**Handling procedures :** Use only in well ventilated areas

Keep away from heat and sources of ignition Do not spray on a naked flame or incandescent

material.

Do not pierce or burn aerosols, even after use.

Do not breathe aerosols or vapours. Avoid contact with skin and eyes.

Storage procedures: Pressurized container: protect from sunlight and do

not expose to temperatures exceeding 50°C. Keep in a cool, dry, well ventilated place

Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

**Control procedures :** Ensure adequate ventilation

Keep away from heat and sources of ignition

Take precautionary measures against static discharges

**Personal protection :** It is advisable to take precautions to avoid contact

with skin and eyes when handling the product.

Use only in well ventilated areas

**inhalation**: In case of insufficient ventilation, wear suitable

respiratory equipment.

(Filter type AX)

hands and skin: Wear suitable protective gloves

(butylrubber)

**eyes:** Wear safety goggles.

**Exposure limits:** 

Hazardous ingredient	CAS-nr	method	
EU established exposure limits:			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm
		STEL	100 ppm
dimethyl ether	115-10-6	TWA	1000 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm



Productname: ZINC Creationdate:

**Ref.Nr.:** AB13900-3-311007 **Replaces:** 28.10.05

Hazardous ingredient	CAS-nr	method	
		STEL	300 ppm

31.10.07

#### 9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state : DME propelled liquid

colour: grey

**odour**: Characteristic odour

Melting point/range : <-20  $^{\circ}C$ 

Boiling point/range : not available

Relative density:  $1.431 \text{ g/cm} 3 \text{ (@ } 20^{\circ}\text{C)}$ 

pH:not applicableVapour pressure:not availableRelative vapour density:not available

Solubility in water : Insoluble in water

Partition coefficient n-octanol/water: not available

Flash point :  $$<0\,^{\circ}\text{C}$$ Auto-ignition :  $$>250\,^{\circ}\text{C}$$ Viscosity : not available
Evaporation rate : not available

#### 10. STABILITY AND REACTIVITY

Conditions to be avoided: Pressurized container: protect from sunlight and do

not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition

Materials to be avoided : Strong oxidising agent

Hazardous decomposition compounds: CO,CO2

#### 11. TOXICOLOGICAL INFORMATION

**Inhalation:** Excessive inhalation of solvent vapours may give rise

to nausea, headaches and dizziness

**Skin contact**: Prolonged skin contact will result in defatting of the

skin, leading to irritation, and in some cases,

dermatitis

**Eye contact**: May cause irritation.

#### 12. ECOLOGICAL INFORMATION

Other adverse effects: Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.



**Productname:** ZINC

**Ref.Nr.:** AB13900-3-311007

**Creationdate :** 31.10.07 **Replaces:** 28.10.05

Do not allow to enter public sewers and watercourses

#### 13. WASTE DISPOSAL

**Product**: Do not empty into drains.

This material and its container must be disposed of in

a safe way.

Disposal should be in accordance with local, state or

national legislation

## 14. TRANSPORT

**UN-number**: 1950

Road/Rail - ADR/RID: UN1950 Aerosols Class: 2, PG: NA, Class code: 5F,

Label : 2.1

Sea - IMDG: UN1950 Aerosols Ltd Qty Class: 2.1, PG: NA, Label

: 2.1

EmS F-D,S-U

Air - IATA/ICAO : UN1950 Aerosols, flammable Class : 2.1, PG : NA,

Label: RFG

 Packing instr. LQ
 Y203

 PAX
 203

 CAO
 203

## 15. REGULATORY INFORMATION

Warning symbol(s): F+N

**Risk-phrase(s)**: R12: Extremely flammable.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or

cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety-phrase(s): S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No

smoking.

S23: Do not breathe spray.

S35: This material and its container must be disposed

of in a safe way.

S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Without adequate ventilation formation of explosive mixtures may be possible.



# Material Safety Data SheetRegulation EC No 1907/2006 Art.31Productname:ZINCCreationdate:31.10.07Ref.Nr.:AB13900-3-311007Replaces:28.10.05

#### **16. OTHER INFORMATION**

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

\*Explanation risk-phrases:

R10: Flammable.

R11: Highly flammable. R12: Extremely flammable. R36: Irritating to eyes.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or

cracking.

R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

